



**CASASCAPES RUBBER, PAINT & TAR REMOVER
FOR CONCRETE PAVERS, WETCAST & NATURAL STONES**

TDS Revision Date (dd/mm/yyyy): 02/04/2020

TECHNICAL DATA SHEET

Update: April 2, 2020
Make sure you have an updated data sheet on hand.
Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

Description: **CASASCAPES RUBBER, PAINT AND TAR REMOVER** is effective in removing rubber, paint and tar from the surface of concrete pavers, wetcast & natural stones.

Features:

- Washes off with water.
- Easy to use.

For use on: For concrete pavers, wetcast & natural stones that are warm to the touch

Please note:

1. This product dissolves sealants.
2. Do not let product dry up on paver surface.
3. Wear goggles and rubber gloves.
4. Use at above 60°F (16°C) in dry conditions.

Application instructions:

1. Apply product to stain.
2. Let it soak for 5 minutes.
3. Apply product again.
4. Immediately scrub with hard bristle brush.
5. Repeat steps 3 & 4 until stain dissolves.
6. Rinse thoroughly with water.

Packaging:	Product	Size	per Box	per Pallet
	CASASCAPES RUBBER, PAINT & TAR REMOVER	946 ml (1 QT.)	6 units	24 boxes

LIMITED WARRANTY:

CASASCAPES INC. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation of CASASCAPES INC. is to refund the purchase price. Proof of purchase is required for any claim. CASASCAPES INC. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, CASASCAPES INC. excludes any implied warranty of quality, merchantability or fitness for purpose.

*Please store container at above 32°F / 0°C.



**CASASCAPES RUBBER, PAINT & TAR REMOVER
FOR CONCRETE PAVERS, WETCAST & NATURAL STONES**

TDS Revision Date (dd/mm/yyyy): 02/04/2020

CONTENTS HARMFUL. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. MAY IRRITATE EYES. MAY IRRITATE SKIN. FUMES MAY CATCH FIRE. Do not mix with other household chemicals. Do not swallow. Do not breathe fumes. Do not get in eyes. Do not get on skin or clothing. Do not smoke. Keep out of reach of children. Wear a mask. Use only in a well ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor.

FIRST AID TREATMENT:

Contains Xylenes, 2-Butoxyethanol, Isopropanol and Alkylated benzene. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for at least 15 minutes. If on skin, rinse well with water.



DANGER
POISON IRRITANT FLAMMABLE